

*AHELP for CIAO 3.4*

_NARGS

Context: [slangrtl](#)*Jump to:* [Description](#) [Example](#) [See Also](#)

Synopsis

The number of parameters passed to a function

Syntax

```
Integer_Type _NARGS
```

Description

The value of the _NARGS variable represents the number of arguments passed to the function. This variable is local to each function.

Example

This example uses the _NARGS variable to print the list of values passed to the function:

```
define print_values ()
{
    variable arg;

    if (_NARGS == 0)
    {
        message ("Nothing to print");
        return;
    }
    foreach (__pop_args (_NARGS))
    {
        arg = ();
        vmessage ("Argument value is: %S", arg.value);
    }
}
```

See Also

slangrtl

class_id, class_type, eqs, get_reference, is_initialized, pop_args, push_args, nargs,
typeof, array_info, dup, is_defined, is_struct_type, length, typecast, typeof

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/_NARGS.tm.html
Last modified: December 2006