

*AHELP for CIAO 3.4*

__get_reference

Context: [slangrtl](#)*Jump to:* [Description](#) [Example](#) [See Also](#)

Synopsis

Get a reference to a global object

Syntax

```
Ref_Type __get_reference (String_Type nm)
```

Description

This function returns a reference to a global variable or function whose name is specified by nm. If no such object exists, it returns NULL, otherwise it returns a reference.

Example

For example, consider the function:

```
define runhooks (hook)
{
    variable f;
    f = __get_reference (hook);
    if (f != NULL)
        @f ();
}
```

This function could be called from another S-Lang function to allow customization of that function, e.g., if the function represents a mode, the hook could be called to setup keybindings for the mode.

See Also

slangrtl

[class_id](#), [class_type](#), [eqs](#), [get_defined_symbols](#), [is_initialized](#), [pop_args](#), [push_args](#), [uninitialize](#), [apropos](#), [function_name](#), [nargs](#), [typeof](#), [array_info](#), [autoload](#), [dup](#), [eval](#), [evalfile](#), [getenv](#), [is_defined](#), [is_struct_type](#), [length](#), [make_printable_string](#), [set_slang_load_path](#), [typecast](#), [typeof](#)

Ahelp: __get_reference – CIAO 3.4

The Chandra X-Ray Center (CXC) is operated for NASA by the
Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/_get_reference.tm.html
Last modified: December 2006