



 AHELP for CIAO 3.4

chips_auto_redraw

Context: [chips](#)

Jump to: [Description](#) [Examples](#) [Bugs](#) [See Also](#)

Synopsis

Set the automatic redrawing mode.

Syntax

```
Integer_Type chips_auto_redraw(flag)
```

Description

This function sets (flag = 1) or unsets (flag = 0) the automatic redrawing mode of ChIPS. It returns the previous setting.

Use the "chips_redraw()" command to force the ChIPS display to be redrawn.

Arguments for chips_auto_redraw

Name	Type	Options	Default	Comment
flag	Integer_Type	0 for off, 1 for on	1 (on)	

Example 1

```
chips> chips_auto_redraw(0)
1
```

Here we have turned off the automatic redraw mode. The return value shows that the previous setting had been on (i.e. 1).

Example 2

```
() = chips_auto_redraw(0);
```

As the first example, but done in a S-Lang script. Here the return value is ignored.

Bugs

See the [bugs page for ChIPS](#) on the CIAO website for an up-to-date listing of known bugs.

See Also

chips

[chips clear](#), [chips color name](#), [chips color value](#), [chips get pane](#), [chips get xrange](#), [chips get xscale](#), [chips get yrange](#), [chips get yscale](#), [chips get zrange](#), [chips get zscale](#), [chips label](#), [chips line](#), [chips pickpoints](#), [chips redraw](#), [chips set pane](#), [chips set xrange](#), [chips set xscale](#), [chips set yrange](#), [chips set yscale](#), [chips set zrange](#), [chips set zscale](#), [chips split](#), [chips version](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/chips_auto_redraw.html
Last modified: December 2006