



AHELP for CIAO 3.4

chips_redraw

Context: [chips](#)*Jump to:* [Description](#) [Examples](#) [Bugs](#) [See Also](#)

Synopsis

Redraws all plotting objects.

Syntax

```
chips_redraw()
```

Description

This is a S-Lang version of the ChIPS REDRAW command. Since it has no parameters, it can be called without the "()".

Use the `chips_auto_redraw()` command to set/unset the automatic redrawing of plots.

Example 1

```
chips> chips_redraw
```

Redraws everything in the plotting window.

Example 2

```
chips_redraw;
```

As the first example, but done in a S-Lang script.

Bugs

See the [bugs page for ChIPS](#) on the CIAO website for an up-to-date listing of known bugs.

See Also

chips

[chips auto redraw](#), [chips clear](#), [chips color name](#), [chips color value](#), [chips get pane](#),

Ahelp: chips_redraw – CIAO 3.4

chips get xrange, chips get xscale, chips get yrange, chips get yscale, chips get zrange,
chips get zscale, chips label, chips line, chips pickpoints, chips set pane, chips set xrange,
chips set xscale, chips set yrange, chips set yscale, chips set zrange, chips set zscale,
chips split, chips version

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/chips_redraw.html
Last modified: December 2006