

*AHELP for CIAO 3.4*

errors

Context: [sherpa](#)*Jump to:* [Description](#) [Examples](#) [Bugs](#) [See Also](#)

Synopsis

Defines an expression to be used to specify the statistical errors for source data.

Syntax

```
sherpa> ERRORS [<dataset range> | ALLSETS] = <errorExpr>
```

where <dataset range> = #, or more generally #:#, #:#, ..., such that # specifies a dataset number, and #:# represents an inclusive range of datasets; one may specify multiple inclusive ranges by separating them with commas. The default dataset is dataset 1.

Description

The error expression, <errorExpr>, may be composed of one, or more (algebraically–combined) of the following elements:

Component:	Description:
DATA	An input dataset
numericals	Numerical values
operators	+ - * / ()

A few things to note:

- Error expressions cannot be defined without first reading in a source dataset.
- The errors can be specified in an input file; see READ ERRORS for more information.
- If the errors are not defined using ERRORS or input using READ ERRORS, then they are computed as defined for the current statistic; see the documentation on the command STATISTIC.

See the related command SYSERRORS.

The errors are accessible to the Sherpa/S–Lang module user via the functions `get_errors` and `set_errors`.

Example 1

Define an expression to be used for the errors. They are set to one-half of the data value in each bin.

```
sherpa> DATA example.dat
sherpa> ERRORS = (0.5)*(DATA)
```

Example 2

Define an expression to be used for the errors. They are set to be the sum of the datum and 2.7 in each bin.

```
sherpa> DATA example.dat
sherpa> ERRORS 1 = DATA + 2.7
```

Bugs

See the [Sherpa bug pages](#) online for an up-to-date listing of known bugs.

See Also

sherpa

[berrors](#), [bsyserrors](#), [compute_errors](#), [compute_statistic](#), [covariance](#), [ftest](#), [get_paramest](#),
[get_paramestint](#), [get_paramestlim](#), [get_paramestreg](#), [goodness](#), [interval-projection](#),
[interval-uncertainty](#), [list_paramest](#), [mlr](#), [projection](#), [region-projection](#), [region-uncertainty](#),
[restore_paramest](#), [run_paramest](#), [run_paramestint](#), [run_paramestlim](#), [run_paramestreg](#), [set_errors](#),
[set_syserrors](#), [staterrors](#), [syserrors](#), [uncertainty](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.

60 Garden Street, Cambridge, MA 02138 USA.

Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:

<http://cxc.harvard.edu/ciao3.4/errors.html>

Last modified: December 2006