



AHELP for CIAO 3.4

is_defined

Context: [slangrtl](#)*Jump to:* [Description](#) [Example](#) [See Also](#)

Synopsis

Indicate whether a variable or function defined.

Syntax

```
Integer_Type is_defined (String_Type obj)
```

Description

This function is used to determine whether or not a function or variable whose name is `obj` has been defined. If `obj` is not defined, the function returns 0. Otherwise, it returns a non-zero value that depends on the type of object `obj` represents. Specifically, it returns one of the following values:

```
+1 if an intrinsic function
+2 if user defined function
-1 if intrinsic variable
-2 if user defined variable
0 if undefined
```

Example

For example, consider the function:

```
define runhooks (hook)
{
  if (2 == is_defined(hook)) eval(hook);
}
```

This function could be called from another S-Lang function to allow customization of that function, e.g., if the function represents a mode, the hook could be called to setup keybindings for the mode.

See Also

slangrtl

[class id](#), [class type](#), [eqs](#), [get defined symbols](#), [get reference](#), [is initialized](#),
[pop args](#), [push args](#), [uninitialize](#), [apropos](#), [function name](#), [nargs](#), [typeof](#), [array info](#),
[autoload](#), [dup](#), [eval](#), [evalfile](#), [getenv](#), [is struct type](#), [length](#), [make printable string](#),
[set slang load path](#), [typecast](#), [typeof](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/is_defined.tm.html
Last modified: December 2006