

*AHELP for CIAO 3.4*

method

Context: [sherpa](#)*Jump to:* [Description](#) [Examples](#) [Bugs](#) [See Also](#)

Synopsis

Specifies the optimization method. The command SEARCHMETHOD is equivalent.

Syntax

```
sherpa> {METHOD | SEARCHMETHOD} <sherpa_methodname>
```

Description

The following optimization methods are featured in Sherpa:

Description of Sherpa's Optimization Methods

<sherpa_methodname>	Description
GRID	A grid search of parameter space, with no optimization.
GRID-POWELL	A grid search of parameter space, with optimization done starting from each grid point, using the Powell method.
{LEVENBERG-MARQUARDT LEV-MAR LM}	Levenberg–Marquardt optimization.
MONTECARLO	A Monte Carlo search of parameter space, with no optimization.
MONTE-LM	A Monte Carlo search of parameter space, with optimization done starting from each randomly selected point, using the LEVENBERG-MARQUARDT method.
MONTE-POWELL	A Monte Carlo search of parameter space, with optimization done starting from each randomly selected point, using the POWELL method.
POWELL	Powell optimization.
{SIGMA-REJECTION SIG-REJ}	Optimization combined with data cleansing: outliers are filtered from the data.
SIMPLEX	Simplex optimization.
SIMUL-ANN-1	A simulated annealing search, with one parameter varied at each step and no optimization.

SIMUL-ANN-2	A simulated annealing search, with all parameters varied at each step and no optimization.
SIMUL-POW-1	A combination of SIMUL-ANN-1 with POWELL optimization.
SIMUL-POW-2	A combination of SIMUL-ANN-2 with POWELL optimization.
USERMETHOD	A user-defined method of optimization.

The default optimization method in CIAO 3.0 is LEVENBERG–MARQUARDT.

The current optimization method, and its parameter names and values, may be listed with the command SHOW METHOD. Values for these optimization parameters may be set individually using one of the following command syntax options:

```
sherpa> <sherpa_methodname>.paramname = <value>
sherpa> <sherpa_methodname>.paramname.VALUE = <value>
sherpa> <sherpa_methodname>.# = <value>
sherpa> <sherpa_methodname>.#.VALUE = <value>
```

where:

- {<paramname> | <#>}: Specifies the parameter whose value is to be set.
- <value>: The numerical (or string) value to which the parameter should be set.

Parameter listings for each optimization method are given in the Sherpa Methods chapter. (Alternatively, one may peruse the documentation for each <sherpa_methodname>.)

The user may access a string giving the name of the current optimization method via the Sherpa/S–Lang module function get_method_expr.

Example 1

Specify an optimization method to be used; set an optimization parameter value:

```
sherpa> METHOD POWELL
sherpa> SHOW METHOD
Optimization Method: Powell

      Name      Value      Min      Max          Description
      ----      -----      ---      ---          -----
1  iters      2000           1     10000  Maximum number of iterations
2    eps      1e-06      1e-09     1e-03  Fractional accuracy
3    tol      1e-06      1e-08       0.1  Tolerance in lnmnop
4   huge      1e+10      1000     1e+12  Fractional accuracy

sherpa> POWELL.eps = .0009
sherpa> SHOW METHOD
Optimization Method: Powell

      Name      Value      Min      Max          Description
      ----      -----      ---      ---          -----
1  iters      2000           1     10000  Maximum number of iterations
2    eps      9e-04      1e-09     1e-03  Fractional accuracy
3    tol      1e-06      1e-08       0.1  Tolerance in lnmnop
```

4	huge	1e+10	1000	1e+12	Fractional accuracy
---	------	-------	------	-------	---------------------

Example 2

Set an optimization parameter value:

```
sherpa> POWELL.1 = 100
sherpa> SHOW METHOD
Optimization Method: Powell

      Name      Value      Min      Max      Description
      ----      ----      ---      ---      -----
 1  iters      100       1     10000  Maximum number of iterations
 2    eps     1e-06   1e-09     1e-03  Fractional accuracy
 3    tol     1e-06   1e-08      0.1  Tolerance in lnmmnop
 4    huge    1e+10    1000     1e+12  Fractional accuracy
```

Example 3

Set an optimization parameter value:

```
sherpa> POWELL.eps.VALUE = .0007
sherpa> SHOW METHOD
Optimization Method: Powell

      Name      Value      Min      Max      Description
      ----      ----      ---      ---      -----
 1  iters      2000       1     10000  Maximum number of iterations
 2    eps     7e-04   1e-09     1e-03  Fractional accuracy
 3    tol     1e-06   1e-08      0.1  Tolerance in lnmmnop
 4    huge    1e+10    1000     1e+12  Fractional accuracy
```

Example 4

Set an optimization parameter value:

```
sherpa> POWELL.1.VALUE = 100
sherpa> SHOW METHOD
Optimization Method: Powell

      Name      Value      Min      Max      Description
      ----      ----      ---      ---      -----
 1  iters      100       1     10000  Maximum number of iterations
 2    eps     1e-06   1e-09     1e-03  Fractional accuracy
 3    tol     1e-06   1e-08      0.1  Tolerance in lnmmnop
 4    huge    1e+10    1000     1e+12  Fractional accuracy
```

Bugs

See the [Sherpa bug pages](#) online for an up-to-date listing of known bugs.

See Also

sherpa

[get_method](#) [expr](#), [grid](#), [grid-powell](#), [levenberg-marquardt](#), [monte-lm](#), [monte-powell](#), [montecarlo](#), [powell](#), [sigma-rejection](#), [simplex](#), [simul-ann-1](#), [simul-ann-2](#), [simul-pow-1](#), [simul-pow-2](#), [usermethod](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/method.html>
Last modified: December 2006