



AHELP for CIAO 3.4

pget

Context: [tools](#)*Jump to:* [Description](#) [Examples](#) [Parameters](#) [Bugs](#) [See Also](#)

Synopsis

Get parameter values

Syntax

```
pget [-abort] toolname parameter [ parameter2 ... ]
```

Description

'pget' gets the value of the specified parameter(s) from the given parameter file. All redirections and shell evaluations are performed.

Example 1

```
pget dmclist infile
```

Return the value of the infile parameter

Example 2

```
pget dmclist infile opt
```

Returns the value of the infile and opt parameters, one per line.

Example 3

```
pget dmclist infile.p_value
```

Will return the actual string stored in the parameter file for the value field of the parameter. Redirections and shell evaluations are NOT performed.

Example 4

```
pget -abort blah.par boo
```

The '--abort' option causes pget to exit with an error when a parameter file specifies an inappropriate value. For example, if blah.par contained

```
boo,i,h,notaninteger,,, "bad value"
```

the above command would exit with an error, rather than prompting for a valid value (as it would if '--abort' were not given). This can be useful in scripts, where prompting for a valid value could cause a script to hang indefinitely.

Parameters

name	type	ftype	reqd
parameter_file	string	input	yes
parameter	string	input	yes
-abort	notype		

Detailed Parameter Descriptions

Parameter=parameter_file (string required filetype=input)

Parameter file from which to retrieve data

Name (plus optional path) of parameter file to get values from

Parameter=parameter (string required filetype=input)

Name of parameter

Name of parameter to retrieve. Optionally can use the various parameter attributes listed below to return those values.

Parameter Attributes

p_mode	Whether the parameter is prompted for or not
p_value	The value of the parameter. If the parameter is a redirected, this returns the redirection string rather than what the redirection evaluates too.
p_min	Minimum value allowed
p_max	Maximum value allowed
p_prompt	The parameter prompt

Parameter=-abort (notype)

Abort flag

If the parameter file contains an invalid value for the requested parameter, exit with an error (instead of prompting for a valid value).

Bugs

See the [bugs page for this tool](#) on the CIAO website for an up-to-date listing of known bugs.

See Also

concept

[parameter](#)

modules

[paramio](#)

paramio

[paccess](#), [paramclose](#), [paramopen](#), [pget](#), [pgets](#), [plist](#) [names](#), [pquery](#), [pset](#), [punlearn](#)

tools

[dmhistory](#), [dmkeypar](#), [dmmakepar](#), [dmreadpar](#), [paccess](#), [pdump](#), [pline](#), [plist](#), [pquery](#), [pset](#), [punlearn](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian

Astrophysical Observatory.

60 Garden Street, Cambridge, MA 02138 USA.

Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:

<http://cxc.harvard.edu/ciao3.4/pget.html>

Last modified: December 2006

Ahelp: pget – CIAO 3.4