

*AHELP for CIAO 3.4*

set_slang_load_path

Context: [slangrtl](#)

Jump to: [Description](#) [Example](#) [See Also](#)

Synopsis

Set the value of the interpreter's load-path

Syntax

```
set_slang_load_path (String_Type path)
```

Description

This function may be used to set the value of the delimiter-separated search path used by the evalfile and autoload functions for locating files.

Example

```
public define prepend_to_slang_load_path (p)
{
    variable s = stat_file (p);
    if (s == NULL) return;
    if (0 == stat_is ("dir", s.st_mode))
        return;

    variable d = path_get_delimiter ();
    set_slang_load_path (strcat (p, d, get_slang_load_path ()));
}
```

Some applications may not support the built-in load-path searching facility provided by the underlying library.

See Also

slangrtl

[get reference](#), [append to slang load path](#), [autoload](#), [byte compile file](#), [eval](#), [evalfile](#),
[get slang load path](#), [import](#), [is defined](#), [path get delimiter](#), [prepend to slang load path](#), [require](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the
Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:

http://cxc.harvard.edu/ciao3.4/set_slang_load_path.tm.html

Last modified: December 2006