

*AHELP for CIAO 3.4*

sherpa.plot

Context: [sherpa](#)*Jump to:* [Description](#) [Examples](#) [Bugs](#)

Synopsis

Configure appearance of Sherpa plots.

Syntax

```
sherpa.plot.[field]
```

Description

The Sherpa configuration variable (also called "state object") `sherpa.plot` controls appearance of most (not all) of the plots generated with the `CPLOT`, `LPLOT`, `OPLOT` and `SPLOT` commands.

(The exceptions are those plots generated by the commands `LPLOT BACK`; `LPLOT DATA`; `LPLOT BACKFIT`; `LPLOT BFIT`; `LPLOT FIT`; `LPLOT BDELCHI`; `LPLOT BRATIO`; `LPLOT BRESIDUALS`; `LPLOT DELCHI`; `LPLOT RATIO`; `LPLOT RESIDUALS`. For these commands, other configuration variables control the plots appearance.)

The following table lists each field of `sherpa.plot`, with a description and the default value:

Field Name	Description	Default
<code>x_errorbars</code>	Add x-axis error bars to data points (0 = false, 1 = true)	0
<code>y_errorbars</code>	Add y-axis error bars to data points (0 = false, 1 = true)	0
<code>errs_style</code>	Style of error bars	bar
<code>errs_type</code>	Direction of Error bars: up, down (or both)	both
<code>x_log</code>	Log scale for x-axis (0 = false, 1 = true)	0
<code>y_log</code>	Log scale for y-axis (0 = false, 1 = true)	0
<code>curvestyle</code>	Style of curve (e.g., histogram)	step
<code>curvecolor</code>	Curve color	default
<code>symbolstyle</code>	Style of symbols (e.g., triangle, square)	none
<code>symbolcolor</code>	Symbol color	default
<code>symbolsize</code>	Symbol size	2
<code>xlabel_size</code>	Size of x label	1.5
<code>ylabel_size</code>	Size of y label	1.5
<code>zlabel_size</code>	Size of z label	1.5

title_size	Size of title	1.5
tickvals_size	Size of tick values	1.5
prefunc	User S–Lang function executed before the data is plotted	NULL
postfunc	User S–Lang function executed after the data is plotted	NULL

Possible error bar styles: standard, bar.

Possible error bar types: both, none, up, down, dn.

Possible colors: black, blue, cyan, default, green, magenta, red, white, yellow.

Possible curve styles: histo, noline, simpleline, step.

Possible symbol styles: bigpoint, block, circle, cross, diamond, downtri, none, point, soliddiamond, soliddowntri, soliduptri, square, uptri.

The fields `sherpa.plot.prefunc` and `sherpa.plot.postfunc` refer to optional user functions that can be applied to plots before and after the plot is created. Please see the ahelp file `sherpa–plot–hooks` for more information.

Example 1

The `sherpa.plot` settings can be changed at the command line. When assigning a string to a field, the string should be quoted as shown in the second command:

```
sherpa> sherpa.plot.x_log = 1
sherpa> sherpa.plot.curvecolor = "green"
```

Example 2

Create an alias `sp` to `sherpa.plot` and use it.

```
sherpa> variable sp = sherpa.plot
sherpa> sp.x_log = 1
sherpa> sp.curvecolor = "green"
```

Example 3

Use `print` to obtain the information about the current settings of `sherpa.plot`:

```
sherpa> print(sherpa.plot)
x_errorbars      = 0
y_errorbars      = 0
errs_style       = bar
errs_type        = both
x_log            = 0
y_log            = 0
curvestyle      = step
curvecolor       = default
symbolstyle     = none
symbolcolor      = default
symbolsize       = 2
xlabel_size      = 1.5
ylabel_size      = 1.5
zlabel_size      = 1.5
title_size       = 1.5
tickvals_size    = 1.5
```

```
prefunc      = NULL
postfunc     = NULL
```

Bugs

See the [Sherpa bug pages](#) online for an up-to-date listing of known bugs.

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/sherpa.plot.html>
Last modified: December 2006

