



AHELP for CIAO 3.4

stk_delete_current

Context: [stackio](#)

Jump to: [Description](#) [Example](#) [Bugs](#) [See Also](#)

Synopsis

Deletes the current element from the stack.

Syntax

```
Integer_Type stk_delete_current( Stack_Type stack )
```

Description

The `stk_delete_current()` routine deletes the current item in the stack. The remaining items are shifted back and the stack pointer remains at the same position, unless the current item was also last item in the stack. In this case, the pointer is moved back one. If successful, this routine returns 0, and non-zero indicates failure.

Example

```
chips> stk_disp( stk )
-----
Stack position: 2
Stack size: 3
Stack allocated: 100
Stack entries:
1 :a.dat:
2 :b.dat:
3 :c.dat:
-----
chips> () = stk_delete_current( stk )
chips> stk_disp( stk )
-----
Stack position: 2
Stack size: 2
Stack allocated: 100
Stack entries:
1 :a.dat:
2 :c.dat:
-----
```

Bugs

See the [bugs page for the stackio library](#) on the CIAO website for an up-to-date listing of known bugs.

See Also

modules

[stackio](#)

stackio

[stk_append](#), [stk_build](#), [stk_change_current](#), [stk_change_num](#), [stk_close](#), [stk_count](#), [stk_current](#),
[stk_delete_num](#), [stk_disp](#), [stk_expand_n](#), [stk_read_next](#), [stk_read_num](#), [stk_rewind](#), [stk_set_current](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the
Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/stackio_stk_delete_current.html
Last modified: December 2006