



AHELP for CIAO 3.4

xsabsori

Context: [sherpa](#)*Jump to:* [Description](#) [Bugs](#) [See Also](#)

Synopsis

Ionized absorber. XSpec model.

Description

An ionized absorber based on that of Done et al. (1992, ApJ 395, 275) and developed by Magdziarz & Zdziarski. See also Zdziarski et al. (1995, ApJ 438, L63). Photoionization rates are from Reilman & Manson (1979, ApJS 40, 815), who employ the Hartree–Slater approximation (accurate to about 5%), and recombination rates are from Shull & Steenburgh (1982, ApJS 48, 95). The cross–sections are extrapolated with E^{-3} above 5 keV. The abundances are set up by the `xspecabundan` command.

xsabsori Parameters

Number	Name	Description
1	PhoIndx	power law photon index
2	nH	hydrogen column in units of 10^{22} cm^{-2}
3	TempAbs	absorber temperature in K
4	xi	absorber ionization state (L/nR^2), see Done et al. (1992)
5	redshift	redshift, z
6	FeAbund	iron abundance relative to that defined by the <code>xspecabundan</code> command

This information is taken from the [XSpec User's Guide](#). Version 11.3.1 of the XSpec models is supplied with CIAO 3.2.

Bugs

For a list of known bugs and issues with the XSPEC models, please visit the [XSPEC bugs page](#).

See Also

sherpa

[atten](#), [bbody](#), [bbodyfreq](#), [beta1d](#), [beta2d](#), [box1d](#), [box2d](#), [bpl1d](#), [const1d](#), [const2d](#), [cos](#), [delta1d](#), [delta2d](#), [dered](#), [devaucouleurs](#), [edge](#), [erf](#), [erfc](#), [farf](#), [farf2d](#), [fpsf](#), [fpsf1d](#), [frmf](#), [gauss1d](#), [gauss2d](#), [gridmodel](#), [hubble](#), [jdpileup](#), [linebroad](#), [lorentz1d](#), [lorentz2d](#), [models](#), [nbeta](#), [ngauss1d](#), [poisson](#), [polynom1d](#), [polynom2d](#), [powlaw1d](#), [ptsrc1d](#), [ptsrc2d](#), [rsp](#), [rsp2d](#), [schechter](#), [shexp](#), [shexp10](#), [shlog10](#), [shloge](#), [sin](#), [sqrt](#), [steph1d](#), [steplo1d](#), [tan](#), [tpsf](#), [tpsf1d](#), [usermodel](#), [xs](#), [xsacisabs](#), [xsapec](#), [xsbapec](#), [xsbody](#), [xsbodyrad](#), [xsboxrad](#), [xsboxrivr](#), [xsboxpower](#), [xsboxmc](#), [xsboxremss](#), [xsboxvapec](#), [xsc6mekl](#), [xsc6pmekl](#),

Ahelp: xsabsori – CIAO 3.4

[xsc6pvmkl](#), [xsc6vmekl](#), [xscabs](#), [xscemekl](#), [xscevtml](#), [xscflow](#), [xscompbb](#), [xscompls](#), [xscompst](#),
[xscomptt](#), [xsconstant](#), [xscutoffpl](#), [xscyclubs](#), [xsdisk](#), [xsdiskbb](#), [xsdiskline](#), [xsdiskm](#), [xsdisko](#), [xsdiskpn](#),
[xsdust](#), [xsedge](#), [xsequil](#), [xsexpabs](#), [xsexpdec](#), [xsexpfac](#), [xsgabs](#), [xsgaussian](#), [xsgnei](#), [xsgrad](#), [xsgrbm](#),
[xshighecut](#), [xshrefl](#), [xslaor](#), [xslorentz](#), [xsmeka](#), [xsmekal](#), [xsmkcflow](#), [xsnei](#), [xsnotch](#), [xsnpshock](#), [xsnsa](#),
[xsnteea](#), [xspcfabs](#), [xspgpwrlw](#), [xspextrav](#), [xspextriv](#), [xsphabs](#), [xsplabs](#), [xsplcabs](#), [xspesm](#), [xspowerlaw](#),
[xspshock](#), [xspwab](#), [xsraymond](#), [xsredden](#), [xsredge](#), [xsrefsch](#), [xssedov](#), [xssmedge](#), [xsspline](#), [xssrcut](#),
[xssresc](#), [xssssice](#), [xsstep](#), [xstbabs](#), [xstbgrain](#), [xstbvarabs](#), [xsuvred](#), [xsvapec](#), [xsvarabs](#), [xsvbremss](#),
[xsvequil](#), [xsvgnei](#), [xsvmcflow](#), [xsvmeka](#), [xsvmekal](#), [xsvnei](#), [xsvnpshock](#), [xsvphabs](#), [xsvpshock](#),
[xsvraymond](#), [xsvsedov](#), [xswabs](#), [xswndabs](#), [xsxion](#), [xszbbody](#), [xszbremss](#), [xszedge](#), [xszgauss](#),
[xszhighect](#), [xszpcfabs](#), [xszphabs](#), [xszpowerlw](#), [xsztbabs](#), [xszvarabs](#), [xszvfeabs](#), [xszvphabs](#), [xszwabs](#),
[xszwndabs](#)

slang

[usermodel](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/xsabsori.html>
Last modified: December 2006