



Bugs: lightcurve

This tool has been deprecated as of CIAO 3.0; use [dmextract](#) instead.

Bugs

1. *The background GTI is taken to be the same as the input GTI.*
2. *lightcurve can only properly deal with unrotated, rectangular regions.*

If a circle (or any complex region) is given, the area calculated will be the area of a rectangle which completely includes this region (called the "bounding box"). This principally affects background-subtracted lightcurves by overestimating the contribution of the background. The final effect is to give artificially *high* count rates.

Workarounds:

1. Obtain count rates with *any* region, using the tool [dmextract](#).
2. If you *insist* on using `lightcurve`, one could obtain background subtracted lightcurves by extracting lightcurves for source and background *individually*. Then use [dmtcalc](#) to scale and subtract the background lightcurve from the source. Note that the scaling would need to account for the original error of casting a circle into a square.

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/bugs/lightcurve.html>
Last modified: 21 November 2006

Bugs: lightcurve – CIAO 3.4